Nov 09, 2026

Product data sheet

HBK00050H2MC

Characteristics

Voltage transformer, HBK, 50 VA, 230V380V415V/12V24V110V230V, multi-type, center-tapped



Main

Range of product	HBK
Product or component type	Voltage transformer
Transformer rated power in VA	50 VA
Device application	Metering

Complementary

Primary voltage	230/380/415 V
Secondary voltage	12/24/110/230 V
Input output isolation	Non isolated
Input/output type	Multi-input and multi-output
Secondary winding	Center tapped
Type of measurement	Voltage
Rated duty	Uninterrupted

Environment

IP degree of protection	IP20
Standards	IEC 61558-2-2
Operating altitude	2000 m
Ambient air temperature for operation	-5…40 °C
Relative humidity	0…90 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.